卡丽 KARAT。 安装说明书 INSTALLATION INSTRUCTIONS

卡丽角阀 KARAT ANGI F VAI VF

BEFORE YOU BEGIN

Please read these instruction carefully familiarize yourself with the required tools,materials,and installation sepuences. Follow the sections that pertain to your patticular installation. This will help you avoid costly mistakes. In addition to proper installation, read all operating and safety instructions.

All infromation in these instructions is based upon the latest product infromation available at the time of publication. Karat reserves the right to make changes in product characteristics, packageing, or availability at any time without notice.

These instructions contain important care, cleaning, and warranty information, please leave instructions for the consumer

The angle valve is only applicable to the toilet connection. The working pressure (static pressure) is not more than 1.0MPa, and the medium temperature is 4° C

安装之前

请仔细阅读说明书,熟悉所需工具、材料和安装顺序,参 照相关章节完成您所需的安装,以避免昂贵的损失,除了 正确的安装外,请详阅所有的操作和安全说明。

本说明书所含的一切资料均以印刷时所有的最新产品为准, 卡丽公司保留权利随时更改产品特性、包装或供应情况, 恕不另行通知。

本说明书也包含了有关保养、清洁及产品担保等重要信息-请交予用户保存。

角阀仅适用于座便器安装时的搭配连接,工作压力(静压)不大于1.0MPa,介质温度为4℃~90℃。

INSTALLATION


1 HOW TO INSTALLATION THE ANGLE VALVE

Flush the water supply pipes thoroughly to remove debris.Install the escutcheon with the angle valve . Twine P.T.F.E. Raw Material Belt around the extension of angle valve.

安装


1 安装角阀

请先彻底冲洗以及供水管中的杂质,将装饰盖穿入角阀本体上,在角阀的牙纹上缠上生料带。



Install the angle valve into the Outlet on the wall.


如图示,将角阀安装到墙体内。



20190508 -1-

DRAWING

Unit:mm 单位: 毫米



10229T-ZZ-CP

INSTALLATION CHECKOUT

Ensure that all coupling nuts are tight. Turn on the main water supply, and check for leaks. Repair as needed.

安装后检查

确保衔接螺母都已拧紧,开启主水源,检查是否有漏水, 如有请重新拧紧。

CLEANING INSTRUCTIONS

All finishes: Clean the finish with mild soap and warm water. Wipe entire surface completely dry with a clean soft cloth. Many cleaners may contain chemicals, such as ammonia, chlorine, toilet cleaner etc, which could adversely affect the finish and are not recommended for cleaning.

Don't use abrasive cleaners or solvents on angle valve and fittings.

清理说明

清理说明 适用于所有加工处理过的表面:

以中性肥皂水清理产品表面,再以干净的软布彻底擦干整个表面。许多清洁剂,比如氨水、去污粉及洁厕灵等,会对产品表面造成伤害,切勿使用。

有腐蚀性的清洁剂或溶剂不可使用于角阀及其附件上。

ONE -YEARS WARRANTY

Our company provides one years warranty for its drain Our company will, at its election , repair , replace or make appropriate adjustment where our company inspection discloses any such defects occurring in normal usage within warranty.

The warranty, including products, is limited clearly. Our company is not responsible for other damages appeared after the warranty. Also, the warranty dose not cover problems arising from labor charges, incorrect use and installation.

年有限担保

本产品自购买之日起,在正常使用下我司将提供一年的质量担保,经核查后,我司有权决定是修理、更改、还是做适当 的调整。

这里的担保,包括产品都已明确地限制在该担保期内。本公司对以后出现的损坏不负有任何责任。担保也不包括外观损伤,使用不当及未按说明书安装的损失。

Shanghai Kohler International Trade Co., Ltd. Address: Room 324, 2 Xinlin Rd, Waigaoqiao Free Trade

Zone, Shanghai Tel: 400-920-8262 Postcode: 200131

上海科勒国际贸易有限公司 地址: 上海市外高桥保税区新灵路106号2号楼324室 电话: 400-920-8262

邮编: 200131